

Fusion Mineral Paints Rose Gold
Wax/Fusion Mineral Paints Pearl Wax
SDS Preparation Date (mm/dd/yyyy): 12/13/2019

Page 1 of 12

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: **Fusion Mineral Paints Rose Gold Wax/Fusion Mineral Paints Pearl Wax**

Other means of identification : No information available.

Recommended use of the chemical and restrictions on use

: Solid waterproofing wax polish blend.
No restrictions on use known.

Chemical family

: Mixture of: Odorless mineral spirits; Natural wax; Paraffin wax; Pigment

Name, address, and telephone number of the manufacturer:

Clapham's Beeswax Products Ltd.

104 Lee Road
Salt Spring Island, BC, Canada
V8K 2A5

Manufacturer's Telephone # : (250) 653-4765; (800) 667-2939 (Toll Free)

24 Hr. Emergency Tel # : No information available.

Name, address, and telephone number of the supplier:

Refer to manufacturer

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

White to slightly yellow waxy solid / semi-solid. Wax-like odour.

Most important hazards:

Flammable solid. Occupational exposure to the substance or mixture may cause adverse effects. Contains material which can cause cancer. For further information, please refer to section 11 of the SDS.

May cause long lasting harmful effects to aquatic life. Avoid release to the environment. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. See Section 12 for more environmental information.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification:

Flammable solid - Category 1

Carcinogenicity - Category 2

Label elements

Hazard pictogram(s)



Signal Word

DANGER!

Hazard statement(s)

Flammable solid
Suspected of causing cancer.



Fusion Mineral Paints Rose Gold
Wax/Fusion Mineral Paints Pearl Wax
SDS Preparation Date (mm/dd/yyyy): 12/13/2019

Page 2 of 12

SAFETY DATA SHEET

Precautionary statement(s)

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking.
Ground/Bond container and receiving equipment.
Use explosion-proof electrical and ventilating equipment.
Wear protective gloves and eye/face protection.

In case of fire: Use carbon dioxide, dry chemical or foam to extinguish.

IF exposed or concerned: Get medical advice/attention.
Store locked up.
Dispose of contents/container in accordance with local regulation.

Other hazards

Other hazards which do not result in classification:

Toxic fumes, gases or vapours may evolve on burning. May cause slight eye and skin irritation. May cause mild respiratory irritation at higher temperatures. May cause gastrointestinal irritation. In extremely high concentrations, may cause symptoms of central nervous system depression. Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration (% by weight)</u>
Titanium oxide	Anatase Titanic acid anhydride	13463-67-7	0.1 - 1.0
Naphtha (petroleum), heavy alkylate	Odorless mineral spirits	64741-65-7	65.0 - 75.0
Mica	Not available.	12001-26-2	1.0 - 5.0

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

- Ingestion* : If ingested, do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention if symptoms persist.
- Inhalation* : If inhaled, move to fresh air. If breathing is difficult, give oxygen by qualified medical personnel only. If breathing is irregular or stopped, administer artificial respiration. If irritation or symptoms develop, seek medical attention.
- Skin contact* : For skin contact, wash with soap and water while removing contaminated clothing. If irritation or symptoms develop, seek medical attention. Launder clothing before reuse.
- Eye contact* : Flush eyes with water for at least 15 minutes. If irritation or symptoms develop, seek medical attention.

Most important symptoms and effects, both acute and delayed

- : May cause slight eye and skin irritation. Direct eye contact may cause slight redness. Direct skin contact may cause temporary redness.
May cause mild respiratory irritation at higher temperatures. May cause coughing and breathing difficulties.
Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
In extremely high concentrations, which are not expected with normal conditions of handling of this product, may also cause nausea, vomiting, dizziness, drowsiness and other symptoms of central nervous system depression.
Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights. Contains material which may cause cancer, based on animal data.



Fusion Mineral Paints Rose Gold
Wax/Fusion Mineral Paints Pearl Wax
SDS Preparation Date (mm/dd/yyyy): 12/13/2019

Page 3 of 12

SAFETY DATA SHEET

Indication of any immediate medical attention and special treatment needed

: Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

: Carbon dioxide (CO₂); Dry chemical; Alcohol resistant foam; Water fog

Unsuitable extinguishing media

: Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

: Flammable solid. May be ignited if heated to extremely high temperatures. Product may float, and be re-ignited at the water's surface. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure. Toxic fumes, gases or vapours may evolve on burning.

Flammability classification (OSHA 29 CFR 1910.106)

: Flammable solid - Category 1

Hazardous combustion products

: Carbon oxides; Reactive hydrocarbons; Aldehydes; Other unidentified organic compounds.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures

: Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: All persons dealing with the clean-up should wear the appropriate chemically protective equipment. Keep people away from and upwind of spill/leak. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Prevent product from entering drains, sewers, waterways and soil. Avoid release to the environment.

Methods and material for containment and cleaning up

: Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use inert, non-combustible absorbents to assist the pick up of material. Scrape up product and place it into a container for disposal. Keep in properly labelled containers. Contact the proper local authorities. For waste disposal, see Section 13 of the SDS.

Special spill response procedures

: If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).
US CERCLA Reportable quantity (RQ): None known.

In Canada: Contact appropriate local and provincial environmental authorities for assistance and/or reporting requirements.



Fusion Mineral Paints Rose Gold
 Wax/Fusion Mineral Paints Pearl Wax
 SDS Preparation Date (mm/dd/yyyy): 12/13/2019

SAFETY DATA SHEET

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

: Use with adequate ventilation. Avoid breathing fumes, mists or vapors. Wear suitable protective equipment during handling. Wear protective gloves and eye/face protection. Avoid contact with skin, eyes and clothing. Keep away from extreme heat and direct flame. Keep away from incompatibles. Wash thoroughly after handling.

Conditions for safe storage : Store in cool/well-ventilated place. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. Keep away from incompatibles.

Incompatible materials : Strong oxidizing agents (e.g. hydrogen peroxide, nitric acid)

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Titanium oxide	10 mg/m ³	N/Av	15 mg/m ³ (total dust)	N/Av
Naphtha (petroleum), heavy alkylate	N/Av	N/Av	500 ppm (2000 mg/m ³) (as petroleum distillates, naphtha)	N/Av
Mica	3 mg/m ³ (respirable)	N/Av	20 mppcf	N/Av

Exposure controls

Ventilation and engineering measures

: Provide adequate ventilation. Apply technical measures to comply with the occupational exposure limits. Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Use explosion-proof electrical and ventilating equipment. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection

: None required when used as intended.
 If airbourne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02. Advice should be sought from respiratory protection specialists.

Skin protection

: For prolonged or repeated skin contact use suitable protective gloves. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Wear sufficient clothing to prevent skin contact.

Eye / face protection

: Wear as appropriate: Tightly fitting safety goggles; Safety glasses with side shields.

Other protective equipment

: Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.

General hygiene considerations

: Avoid breathing fumes, mists or vapors. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.



Fusion Mineral Paints Rose Gold
Wax/Fusion Mineral Paints Pearl Wax
SDS Preparation Date (mm/dd/yyyy): 12/13/2019

Page 5 of 12

SAFETY DATA SHEET

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : White to slightly yellow waxy solid / semi-solid.
Odour : Wax-like odour.
Odour threshold : N/Av
pH : N/Av
Melting Point/Freezing point : N/Av
Initial boiling point and boiling range
: > 150°C (302°F) (based on ingredients)
Flash point : 40.5°C (105°F)
Flashpoint (Method) : ASTM D 56
Evaporation rate (BuAe = 1) : < 1 (butyl acetate = 1)
Flammability (solid, gas) : Flammable solid
Lower flammable limit (% by vol.)
: N/Av
Upper flammable limit (% by vol.)
: N/Av
Oxidizing properties : None known.
Explosive properties : Not explosive
Vapour pressure : N/Av
Vapour density : > 1 (Air = 1.0)
Relative density / Specific gravity
: 0.8
Solubility in water : Insoluble.
Other solubility(ies) : N/Av
Partition coefficient: n-octanol/water or Coefficient of water/oil distribution
: N/Av
Auto-ignition temperature : N/Av
Decomposition temperature : N/Av
Viscosity : > 60 cSt @ 40°C (104°F)
Volatiles (% by weight) : N/Av
Volatile organic Compounds (VOC's)
: N/Av
Absolute pressure of container
: N/Av
Flame projection length : N/Av
Other physical/chemical comments
: No additional information.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions
: Hazardous polymerization does not occur.
Conditions to avoid : Keep away from extreme heat and flame. Do not use in areas without adequate ventilation. Avoid contact with incompatible materials.
Incompatible materials : Strong oxidizing agents (e.g. hydrogen peroxide, nitric acid)



Fusion Mineral Paints Rose Gold
Wax/Fusion Mineral Paints Pearl Wax
SDS Preparation Date (mm/dd/yyyy): 12/13/2019

Page 6 of 12

SAFETY DATA SHEET

Hazardous decomposition products

: None known, refer to hazardous combustion products in Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES

Routes of entry skin & eye : YES

Routes of entry Ingestion : YES

Routes of exposure skin absorption
: NO

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

: May cause mild respiratory irritation at higher temperatures. May cause coughing and breathing difficulties. In extremely high concentrations, which are not expected with normal conditions of handling of this product, may also cause nausea, vomiting, dizziness, drowsiness and other symptoms of central nervous system depression.

Sign and symptoms ingestion

: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sign and symptoms skin

: Direct skin contact may cause slight or mild, transient irritation. Direct skin contact may cause temporary redness.

Sign and symptoms eyes

: Direct eye contact may cause slight or mild, transient irritation. Direct eye contact may cause temporary redness.

Potential Chronic Health Effects

: Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights.

Mutagenicity

: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Carcinogenicity - Category 2 Suspected of causing cancer. Contains Titanium dioxide. Titanium dioxide is classified as possibly carcinogenic by IARC (Group 2B).

Reproductive effects & Teratogenicity

: This product is not expected to cause reproductive or developmental effects.

Sensitization to material

: Not expected to be a skin or respiratory sensitizer.

Specific target organ effects

: According to the classification criteria of U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015), this product is not expected to cause target organ toxicity through single or repeated exposures.

Mild effects may be seen in the following organs: Eyes; Skin; Respiratory system; Digestive system; Liver; Kidneys

Medical conditions aggravated by overexposure

: Pre-existing skin, eye and respiratory disorders.

Synergistic materials

: None reported by the manufacturer.

Fusion Mineral Paints Rose Gold
Wax/Fusion Mineral Paints Pearl Wax
SDS Preparation Date (mm/dd/yyyy): 12/13/2019

Page 7 of 12

SAFETY DATA SHEET

Toxicological data : Not classified for acute toxicity based on available data. No data is available on the product itself.

See below for individual ingredient acute toxicity data.

<u>Chemical name</u>	<u>LC₅₀(4hr)</u> <u>inh. rat</u>	<u>LD₅₀</u>	
		<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Titanium oxide	> 6.82 mg/kg (dust) (No mortality)	> 25 000 mg/kg	> 10 000 mg/kg
Naphtha (petroleum), heavy alkylate	23.78 mg/L (vapour) (Read-across)	> 5000 mg/kg	> 2000 mg/kg (No mortality)
Mica	N/Av	> 15 000 mg/kg	N/Av

Other important toxicological hazards

: None reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity : May cause long lasting harmful effects to aquatic life.
No data is available on the product itself. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

See the following tables for individual ingredient ecotoxicity data.

Ecotoxicity data:

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Fish</u>		
		<u>LC50 / 96h</u>	<u>NOEC / 21 day</u>	<u>M Factor</u>
Titanium oxide	13463-67-7	> 100 mg/L (Japanese ricefish)	N/Av	None.
Naphtha (petroleum), heavy alkylate	64741-65-7	N/Av	N/Av	None.

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Daphnia</u>		
		<u>EC50 / 48h</u>	<u>NOEC / 21 day</u>	<u>M Factor</u>
Titanium oxide	13463-67-7	> 100 mg/L (Daphnia magna)	N/Av	None.
Naphtha (petroleum), heavy alkylate	64741-65-7	N/Av	N/Av	None.

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Algae</u>		
		<u>EC50 / 96h or 72h</u>	<u>NOEC / 96h or 72h</u>	<u>M Factor</u>
Titanium oxide	13463-67-7	> 100 mg/L/72hr (Green algae)	N/Av	None.
Naphtha (petroleum), heavy alkylate	64741-65-7	13 mg/L/72hr (Green algae)	N/Av	None.



Fusion Mineral Paints Rose Gold
Wax/Fusion Mineral Paints Pearl Wax
 SDS Preparation Date (mm/dd/yyyy): 12/13/2019

SAFETY DATA SHEET

Persistence and degradability

: The product itself has not been tested.
 Contains the following chemicals which are considered to be inherently biodegradable:
 Odorless mineral spirits.

Bioaccumulation potential

: The product itself has not been tested. See the following data for ingredient information.

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)	7	598 - 11,430
Mica (CAS 12001-26-2)	N/Ap	N/Ap

Mobility in soil

: The product itself has not been tested.

Other Adverse Environmental effects

: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal

: Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.

Methods of Disposal

: Dispose in accordance with all applicable federal, state, provincial and local regulations.

RCRA

: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
TDG	UN3175	SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Odorless mineral spirits)	4.1	II	
TDG Additional information	May be shipped as Limited Quantity when transported in containers no larger than 1.0 kg; total per package may not exceed 30 kg gross mass. Under the TDG, refer to Section 1.17 for additional exemption requirements, if shipping under this exemption.				
49CFR/DOT	UN3175	Solids containing flammable liquid, n.o.s. (Odorless mineral spirits)	4.1	II	
49CFR/DOT Additional information	May be shipped as Limited Quantity when transported in containers no larger than 1.0 kg; total per package may not exceed 30 kg gross mass. Refer to 49 CFR Section 173.151.				

Special precautions for user : Appropriate advice on safety must accompany the package.

Environmental hazards

: This product does not meet the criteria for an environmentally hazardous mixture, according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.



Fusion Mineral Paints Rose Gold
 Wax/Fusion Mineral Paints Pearl Wax
 SDS Preparation Date (mm/dd/yyyy): 12/13/2019

SAFETY DATA SHEET

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

Ingredients	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de minimus Concentration
Titanium oxide	13463-67-7	Yes	None.	None.	No	No
Naphtha (petroleum), heavy alkylate	64741-65-7	Yes	None.	None.	No	No
Mica	12001-26-2	No	N/Ap	N/Ap	No	No

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes:

Physical hazards (Flammable solid)Health hazards(Carcinogenicity)
 Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

Ingredients	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Titanium oxide	13463-67-7	Yes	Cancer (airborne, unbound particles of respirable size)	No	Yes	Yes	Yes	Yes	Yes
Naphtha (petroleum), heavy alkylate	64741-65-7	No	N/Ap	No	No	No	No	No	No
Mica	12001-26-2	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

Canadian National Pollutant Release Inventory (NPRI): This product contains the following substances listed on the NPRI:

Odorless mineral spirits (Part 5: Other groups and mixtures)
 WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

International Information:

Components listed below are present on the following International Inventory list:



Fusion Mineral Paints Rose Gold
 Wax/Fusion Mineral Paints Pearl Wax
 SDS Preparation Date (mm/dd/yyyy): 12/13/2019

SAFETY DATA SHEET

<u>Ingredients</u>	CAS #	European EINECS	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	NewZealand IOC
Titanium oxide	13463-67-7	236-675-5	Present	Present	(5)-5225; (1)-558	KE-33900	Present	May be used as a single component chemical under an appropriate group standard.
Naphtha (petroleum), heavy alkylate	64741-65-7	265-067-2	Present	Present	(9)-1690	KE-18190	Present	May be used as a single component chemical under an appropriate group standard.
Mica	12001-26-2	None. This chemical may be grouped under the name 'Naturally occurring substances' with the following EINECS number: 310-127-6	Present	Present	Not listed	KE-25420	Present	May be used as a single component chemical under an appropriate group standard.

SECTION 16. OTHER INFORMATION

Legend

- : ACGIH: American Conference of Governmental Industrial Hygienists
- AICS: Australian Inventory of Chemical Substances
- ATE: Acute Toxicity Estimate
- CA: California
- CAS: Chemical Abstract Services
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
- CFR: Code of Federal Regulations
- CSA: Canadian Standards Association
- DOT: Department of Transportation
- EC50: Effective Concentration 50%
- EINECS: European Inventory of Existing Commercial chemical Substances
- ENCS: Existing and New Chemical Substances
- EPA: Environmental Protection Agency
- HSDB: Hazardous Substances Data Bank
- IARC: International Agency for Research on Cancer
- IBC: Intermediate Bulk Container
- IECSC: Inventory of Existing Chemical Substances
- IMDG: International Maritime Dangerous Goods
- IOC: Inventory of Chemicals
- KECI: Korean Existing Chemicals Inventory
- KECL: Korean Existing Chemicals List
- LC: Lethal Concentration
- LD: Lethal Dose
- MA: Massachusetts
- MN: Minnesota
- N/Ap: Not Applicable
- N/Av: Not Available



Fusion Mineral Paints Rose Gold
Wax/Fusion Mineral Paints Pearl Wax
SDS Preparation Date (mm/dd/yyyy): 12/13/2019

SAFETY DATA SHEET

NIOSH: National Institute of Occupational Safety and Health
NJ: New Jersey
NOEC: No observable effect concentration
NTP: National Toxicology Program
OECD: Organisation for Economic Co-operation and Development
OSHA: Occupational Safety and Health Administration
PA: Pennsylvania
PEL: Permissible exposure limit
PICCS: Philippine Inventory of Chemicals and Chemical Substances
RCRA: Resource Conservation and Recovery Act
RI: Rhode Island
RTECS: Registry of Toxic Effects of Chemical Substances
SARA: Superfund Amendments and Reauthorization Act
SDS: Safety Data Sheet
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Identification System

References

1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2018.
2. International Agency for Research on Cancer Monographs, searched 2019.
3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2019 (Chempendium, HSDB and RTECs).
4. Safety Data Sheets from manufacturer.
5. US EPA Title III List of Lists - June 2019 version.
6. California Proposition 65 List - September 2019 version.
7. OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2019.

Preparation Date (mm/dd/yyyy)

: 12/13/2019

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

<p>Prepared for: Clapham's Beeswax Products Ltd. 104 Lee Road Salt Spring Island, BC, Canada, V8K 2A5 Telephone: (250) 653-4765 Direct all enquiries to: Clapham's Beeswax Products Ltd.</p>	
<p>Prepared by: ICC The Compliance Center Inc. Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada) http://www.thecompliancecenter.com</p>	

DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Clapham's Beeswax Products Ltd. and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Clapham's Beeswax Products Ltd. expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.



Clapham's Beeswax Products Ltd.
104 Lee Road
Salt Spring Island, BC, Canada, V8K 2A5
Telephone: (250) 653 4765

**Fusion Mineral Paints Rose Gold
Wax/Fusion Mineral Paints Pearl Wax
SDS Preparation Date (mm/dd/yyyy): 12/13/2019**

Page 12 of 12

SAFETY DATA SHEET

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Clapham's Beeswax Products Ltd.

END OF DOCUMENT