

Fusion Mineral Paint
101 Portland Street
Etobicoke, ON, M8Y 1B1
Canada
1-877-886-5098

PRODUCT: FUSION PAINT COLOURS**SECTION 01: IDENTIFICATION**

Initial supplier identifier..... Fusion Mineral Paint
101 Portland Street
Etobicoke
Ontario
Canada
M8Y 1B1
1877-886-5098

Product identifier..... FUSION PAINT COLOURS

Recommended use and restrictions Paint for consumer use.

Chemical family..... Water based paint mixture.

Emergency telephone number and any ... (613)-541-0299 (9am to 4:30pm EST).
restrictions

SECTION 02: HAZARD IDENTIFICATION

Hazard Classification..... Non-toxic - does not meet OSHA Hazard Communication classification criteria. Does not meet any hazard criteria defined by the Hazardous Products Regulations 2015.

Signal Word..... Not hazardous.

Precautionary Statements..... Avoid prolonged contact with skin. Avoid contact with eyes. Wash skin thoroughly after handling. Do not ingest this product and wash hands before consuming food. .

Hazard Description..... Direct skin contact may result in little or no irritation. Prolonged contact, may be more irritating. Eye contact may cause mild transient irritation. If ingested, may cause irritation of mouth, throat, and stomach. Swallowing may cause irritation, nausea and vomiting. Ingestion of larger amounts may cause defects to the central nervous system (e.g. dizziness, headache).

Mixtures Statement..... The product label has been evaluated in accordance with ASTM-4236.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
----------------------------	-------	-------

* Carbon Black is an ingredient in the following colours: Algonquin, ---
Ash, Bedford, Casement, Cathedral Taupe, Champlain, Chocolate,
Coal Black, Cranberry, Homestead Blue, Lamp White, Laurentien,
Lichen, Linen, Midnight Blue, Putty, Raw Silk, Seaside, Soap Stone,
and Sterling

*Titanium Dioxide is an ingredient in the following colours: Algonquin,
Ash, Azure, Bayberry, Bedford, Brook, Buttermilk Cream, Casement,
Cathedral Taupe, Champlain, Champness, Coral, Cranberry, English
Rose, Heirloom, Homestead Blue, Inglenook, Lamp White,
Laurentien, Lichen, Lily Pond, Limestone, Linen, Mustard, Park
Bench, Pebble, Picket Fence, Putty, Raw Silk, Seaside, Soap Stone,
Sterling, and Tuscan Orange

SECTION 04: FIRST-AID MEASURES

Eye Contact..... Immediately flush eyes with running water for at least 5 to 10 minutes. If irritation persists, seek prompt medical attention.

Ingestion..... Do not induce vomiting. Never give anything by mouth if victim is unconscious. Consult a physician.

Inhalation..... Unintentional inhalation of this product should not pose any health risks. .

Skin Contact..... Wash off with soap and plenty of water. In the unlikely event that irritation occurs, consult with your doctor.

Additional Information..... Treat symptomatically.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing This product does not burn in its liquid form. Use extinguishing media suitable to the
media surrounding fire.

Hazardous Combustion Products..... Carbon oxides in the event the dried paint is involved in a fire.

PRODUCT: FUSION PAINT COLOURS**SECTION 05: FIRE-FIGHTING MEASURES**

Special protective equipment and None required for this product .
 precautions for fire-fighters
 Specific hazards arising from the Not flammable under normal conditions of use. This product is not sensitive to mechanical
 hazardous product impact or static discharge.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions / protective Spills on floors can create a slip hazard. Adequate precautions should be taken when
 equipment walking on spilled product.
 Emergency Procedures..... Keep children and all others away from spilled material.
 Methods / Materials For Containment..... Use suitable absorbent materials such as cloth, rags, sponges, or paper towels .
 Clean Up..... Contain and wipe up the spill with absorbent material or cloth. Rinse the cloth with water
 and repeat the process until surface is clean and dry of spilled material .

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling..... Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Keep away
 from extreme heat and flame. Keep containers tightly closed when not in use.
 Conditions for safe storage, including any Store in a cool, dry, well ventilated area. Do not freeze. Recommended storage
 incompatibilities temperature: 0 - 30°C (32 - 86°F).

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
-------------	-----	-------------------	-----	------------------	-----	-------

Personal protective equipment:..... No personal protective equipment is necessary when handling or using this product.
 Clothing/Type..... No special protective clothing is required to use this product.
 Eye/Type..... Take the necessary precautions to avoid liquid contact with eyes.
 Gloves/Type..... No gloves are required to handle this product.
 Engineering Controls..... No special ventilation requirements are necessary for this product.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Physical Appearance..... Liquid.
 Color..... Various colours.
 Odour..... Mild odour.
 Odour Threshold (ppm)..... No data available.
 Vapour Density (Air = 1)..... No data.
 Vapour Pressure (mm Hg)..... Similar to water.
 pH..... 8.4 - 9.2.
 Relative Density / Specific Gravity..... 1.02-1.67 (calculated).
 Melting / Freezing Point..... 0° C / 32° F.
 Solubility Dilutable in water.
 Initial Boiling Point / Boiling Range..... 100°C / 212°F.
 Evaporation Rate..... Similar to water.
 Flash Point (deg C), Method..... Non-flammable.
 Auto Ignition Temperature (deg C)..... Not applicable.
 Upper Flammable Limit (% Vol)..... Not applicable.
 Lower Flammable Limit (% Vol)..... Not applicable.
 Coefficient of Water/Oil Distribution..... No data.
 Viscosity..... 350 - 500 cps.

SECTION 10: STABILITY AND REACTIVITY

Reactivity..... Avoid extreme heat or freezing temperatures.
 Chemical stability..... Stable under the recommended storage and handling conditions prescribed.
 Possibility of hazardous reactions..... Will not occur.
 Hazardous decomposition products..... None known, refer to hazardous combustion products in Section 5.
 Incompatible materials..... There are no known incompatibilities.
 Note On Decomposition..... Not applicable.

PRODUCT: FUSION PAINT COLOURS**SECTION 11: TOXICOLOGICAL INFORMATION**

INGREDIENTS	LC50	LD50
-------------	------	------

Routes of Exposure:.....	Skin and eye contact are possible routes of exposure. Mists and vapours are unlikely to be generated during intended use of this product. Do not take internally or ingest this product.
Effects Of Acute Exposure.....	Ingestion of large amounts may be harmful. If product is heated or mists are formed, inhalation may cause irritation to the nose, throat and respiratory tract. Direct skin contact may result in little or no irritation. Prolonged contact may be more irritating. Eye contact may cause mild transient irritation. May cause irritation of mouth, throat, and stomach.
Effects Of Chronic Exposure.....	Swallowing may cause irritation, nausea and vomiting.
Carcinogenicity Of Material.....	None known.
Aggravated Medical Conditions.....	Some colours contain titanium dioxide, an IARC Group 2B carcinogen. However, the titanium dioxide used in this product is in a non respirable form and under normal conditions of use, Titanium dioxide cannot become airborne. The carcinogenic effects of titanium dioxide are therefore not applicable to this product. Some colours contain carbon black, an IARC 2B carcinogen. However, the carbon black used in this product is in a non-respirable form and under normal conditions of use carbon black cannot become airborne. The carcinogenic effects of carbon black are therefore not applicable to this product.
Note.....	None are anticipated under normal use.
	Use of this product following our recommended instructions should not cause any health hazards, other than those indicated above .

SECTION 12: ECOLOGICAL INFORMATION

Data From Toxicity Tests.....	Data from toxicity tests are not available at this time .
Environmental.....	No data at this time .
Bioaccumulation Potential.....	No data available at this time.
Other Adverse Effects.....	No data available at this time.
Absorption Potential.....	No data available at this time.

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods.....	Empty containers should be recycled in accordance with local municipal recycling practices. Containers that are not empty should be brought to your local waste paint recycling facility .
Appropriate Disposal Considerations.....	Wherever possible unused paint should be brought to your local waste paint facility.
Properties Affect Disposal.....	None anticipated.
Sewage Disposal Comments.....	Wherever possible, paint should not be washed down the sewer.

SECTION 14: TRANSPORT INFORMATION

UN Number.....	Not regulated.
UN Proper Name.....	Not regulated.
Transport Hazard Class.....	Not regulated.
Packaging Group.....	Not regulated.
Environmental Hazards.....	None known.
Guidance On Transport In Bulk.....	Not regulated.
Guidance on transport by air (IATA).....	This product is not classified as a dangerous good per IATA Dangerous Goods Regulations.
Any Special Precautions.....	None known.

SECTION 15: REGULATORY INFORMATION

GHS Classification.....	Not classified.
WHMIS 1988 Classification.....	Not controlled.
CEPA Status.....	The ingredients in this product appear on the DSL .
TSCA Inventory Status.....	All ingredients are listed on the TSCA inventory.
OSHA.....	This product is not considered hazardous .
SARA TITLE III	
Section 302 - Extremely Hazardous Substances	None.
Section 311/312 - Hazard Categories.....	Not applicable.
SARA Section 313.....	This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above de minimus concentrations.

PRODUCT: FUSION PAINT COLOURS**SECTION 15: REGULATORY INFORMATION**

EPA Hazardous Air Pollutants (HAPS)	None.
40CFR63	
HS Code.....	3213.10.00.00.
California Proposition 65.....	Titanium dioxide is known by the state of California to cause cancer. However, Titanium dioxide is listed when found in unbound, airborne particles of respirable size. Carbon black is known by the state of California to cause cancer. However, Carbon black is listed when found in unbound, airborne particles of respirable size.

SECTION 16: OTHER INFORMATION

Prepared By.....	Trivalent Data Systems Ltd. www.trivalent.com .
Disclaimer.....	This Safety Data Sheet was prepared by Fusion Mineral Paints and obtained from supplier information. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. Fusion Mineral Paints disclaims all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process. This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of Fusion Mineral Paints.
Date of the latest revision of the safety .. data sheet	2023-09-26